

ICY BOX IB-1922MF-C32

External Type-C[®] enclosure for M.2 NVMe SSD

Key features

- High-grade aluminium enclosure with innovative heat sink design
- PCIe 3.0 x4 data transfer rates of up to 20 Gbit/s
- M-Key socket for NVMe SSDs, 22x 30/42/60/80 mm •
- Features a temperature controlled 30 mm fan for active cooling
- Activation of write protection via switch
- Interface to host computer: USB 3.2 (Gen 2x2) Type-C®
- Downward compatible with USB 3.1/3.0/2.0
- Supports Windows®, macOS®

Packing content

1x IB-1922MF-C32, 1x Type-C® to Type-C® cable, 1x Phison PS5012-E12S4 960 GB Gen 3x4 NVMe 1x screwdriver, 1x screw set for M.2 fixation, 1x silicone thermal pad, 1x user manual

External USB Type-C[®] enclosure for M.2 NVMe SSD

Thanks to the external USB 3.2 Type-C[®] enclosure IB-1922MF-C32 you can take one NVMe SSD with you easily enough. It allows access to M.2 SSDs of up to 2 TB no matter to which host you connect it. The IB-1922MF-C32 is compatible with M.2 cards of 30/42/60/80 mm length, it is operating system-independent and suitable for a variety of applications such as high-speed storage, cloning a drive or running a mobile operating system. A PCIe controller from Asmedia provides the NVMe inside the IB-1922MF-C32 with incredible transfer rates of up to 20 Gbit/s for reading and writing and gives your M.2 SSD longevity and efficiency.

Technical data Model Article no.

EAN code

Brand

Colour

Socket

Material

Transfer rate

UASP support

M.2 card size

M.2 interface

SSD capacity

Plug & Play

Cooling

Length of cable

IB-1922MF-C32 with specially designed M.2 NVMe 60792 4250078171287 ICY BOX Anthracite/black Aluminium, plastic Interface to host computer USB 3.2 (Gen 2x2) Type-C® Up to 20 Gbit/s Yes 35 cm M.2 M-Key PCle x4 (NVMe) 22x 30/42/60/80 mm PCle x4 (NVMe) M.2 PCle 3.0 M-Key Supported M.2 card keys Up to 2 TB Yes 30x30 mm fan

Fan noise LED Power supply

~ 22 dB (A) **Operating system** System requirements

Power, access, write protection Bus powered Windows®, macOS® The enclosure only supplies the full data transfer rate of up to

20 Gbit/s via a USB 3.2 (Gen 2x2) Type-C® host interface and an available Asmedia chipset ASM3264 in your host PC.

Currently a macOS® based computer does not support the USB 3.2 (Gen 2x2) standard. A USB Type-A host interface can be connected with USB 3.1, 3.0 or 2.0 standard in some notebooks and computers and can be used with the related data transfer rate via a USB Type-C[®] to type-A cable (not included).

The enclosure also works on devices with a Thunderbolt[™] 3 Type-C[®] interface only with the transfer rate of up to 10 Gbit/s specified by USB 3.1 (Gen 2). The following operating systems are supported: Windows®, macOS®

RaidSonic Technology GmbH • Kurt-Fischer-Straße 50 • 22926 Ahrensburg / Germany Telephone: +49-(0)4102 - 468 900 (Sales) • Fax: +49-(0)4102 - 468 901 • info@raidsonic.de • www.raidsonic.de Offers and deliveries are only done under our General Terms and Conditions. Errors and omissions excepted.





ICY BOX **IB-1922MF-C32** External Type-C[®] enclosure for M.2 NVMe SSD



Smart and cool!

Fan with intelligent temperature control by built-in IC chipset. If the temperature of the device rises above 40° C, the fan starts automatically. If the temperature of the device falls below 40° C, the fan stops automatically.



Simply safe!

With the IB-1922MF-C32, sensitive data can now be protected against alteration and can be released again via switch. With a small hand movement, the switch on the IB-1922MF-C32 can be moved to the desired position. Click - Safe.



Logistical data Packing unit: Total weight: Gross weight (with packing): Net weight:

40 pcs./carton 10.76kg/carton 0.247 kg 0.148 kg

Perfect symbiosis

USB 3.2 (Gen 2x2)-capable connections on computers are far from being standard, even though some of the latest generation of desktop motherboards already have them. This makes it all the more important to pay attention to the new USB specification. If you want to be a technology pioneer, you will be surprised by the incredible data transfer rates of the ICY BOX IB-1922MF-C32 enclosure solution and use the perfect combination with our IB-PCI1901-C32 expansion card!

Dimension/carton: Dimension (with packing): Dimension of article: Country of origin:

440x325x230 mm 30x100x200 mm 102x42x24 mm China

 RaidSonic Technology GmbH • Kurt-Fischer-Straße 50 • 22926 Ahrensburg / Germany

 Telephone: +49-(0)4102 - 468 900 (Sales) • Fax: +49-(0)4102 - 468 901 • info@raidsonic.de • www.raidsonic.de

 Offers and deliveries are only done under our General Terms and Conditions. Errors and omissions excepted.

