



ICY BOX IB-367-CPD+

USB 3.1 Type-C™ (Gen 2) enclosure
for 1x 2,5"/3,5" SATA drives with
Mini DisplayPort™ and PD

Key features

- For 2,5" or 3,5" SATA I/II/III HDD/SSD (up to 6 Gbit/s)
- USB 3.1 Type-C™ (Gen 2) Host port (up to 10 Gbit/s)
- Mini Display Port™ interface for additional 4K monitor
- USB Type-C™ interface supports Power Delivery 2.0 (up to 24 W)
- High-grade aluminium enclosure
- Plug & Play and Hot Swap
- Supports Windows®, MacOS®



Packing content

1x IB-367-CPD+, 1x USB 3.1 Type-C™ (Gen 2) Cable,
1x Power adapter, 1x Manual, 1x screw kit, 2x Keys

More than just an enclosure

The IB-367-CPD+ shines not only with its high transfer rate because of the USB 3.1 Type-C™ interface (up to 10 Gbit/s) and the support of SATA III (up to 6 Gbit/s), but also with the additional possibility to expand a 4K monitor via the Mini DisplayPort™.

Technical data

Model	IB-367-CPD+
Article no.	60611
EAN code	4250078183945
Brand	ICY BOX
Colour	Black
Material	Aluminium
Interface to host computer	USB 3.1 (Gen 2) Type-C™
HDD size	2.5" or 3.5"
HDD height	Up to 20 mm
HDD interface	SATA I/II/III
HDD capacity	Unlimited
UASP support	Yes
Transfer rate	Up to 10 Gbit/s
HotSwap	Yes
Plug & Play	Yes

Video interface	Mini DisplayPort™
Video standard	DisplayPort™ via USB alternate Mode
Max. resolution	3840x2160 pixel
USB Power delivery	PD 2.0 with 5/9/12 V up to 24 W
ON/OFF button	Yes
LED	Power and access
Lock	Yes
Cooling	Passive
Power supply	12 V power adapter
Operating system	Windows®, macOS®
System requirements	USB Type-C™ interface enabled Windows® / macOS® computer. DisplayPort™ Alternate Mode and Power Delivery 2.0 support required! The device is compatible with Thunderbolt™ 3 equipped computers



ICY BOX **IB-367-CPD+**

USB 3.1 Type-C™ (Gen 2) enclosure for 1x 2,5"/3,5" SATA drives with Mini DisplayPort™ and PD



Quick installation

The spring technology of the HDD slot, the toolless mounting, Hot Swap and Plug & Play guarantee a very easy installation of the hard disk.



Simultaneous loading

In addition to the high transfer rate of the USB 3.1 Type-C™ (Gen 2) interface, it is also possible to charge the host device (notebook/handheld device) with up to 24 Watt via this interface. Thus the USB Type-C™ interface is fully exploited and no complications can occur.



A silent pleasure

The high-grade enclosure is solely responsible for the passive dissipation of heat to the environment. This does not require a loud fan, which could interfere with working or watching movies.

Logistical data

Packing unit: 10 pcs./carton
Total weight: 14.9kg/carton
Gross weight (with packing): 1.2 kg
Net weight: 0.719 kg

Dimension/carton: 590x340x290 mm
Dimension (with packing): 110x225x160 mm
Dimension of article: 225x35x130 mm
Country of origin: China