





ICY BOX IB-DK2242AC

DockingStation with Dual DisplayPort[™] interfaces

Key features

- Two DisplayPort™ interfaces up to 4K@60 Hz/each monitor or up to 5K@60 Hz for one Monitor
- Supports both Type- C^{TM} or Type-A host interface two cables included!
- Six USB 3.0, Type-A interfaces supports data transfer rate up to 5 Gbit/s
- Audio input and output ports allows connection of external speakers, headphones or a microphone.
- Supports audio pass through via DisplayPort™ cable to a monitor or TV
- Gigabit LAN RJ45 interface with wake-on-LAN function
- Equipped with power button to save energy and reduce resource consumption
- Including external 45 W power supply (20 V / 2.25 A)



Packing content

IB-DK2242AC, external power supply, 3 pin power cable, USB Type-B to Type-C[™] cable (100 cm), Type-B to USB Type-A cable (100 cm), driver CD, manual

Notebook DockingStation

Notebooks and other mobile devices are getting thinner and smaller. This is usually at the expense of connectivity options - even the widespread RJ45 LAN port or extra USB inputs are often drastically reduced. Concerning video connections that many display devices are required, we'd rather not even talk. With the IB-DK2242AC, any lack of connectors on the PC will become a thing of the past. The connection is simple and is accomplished with a USB 3.0. Once connected, all the additional eleven ports (6x USB 3.0, Gigabit LAN, 2x DisplayPortTM, headphones & microphone) are available. This high quality DockingStation can be used with both current Windows® and macOS® operating systems.

Technical data

Model IB-DK2242AC Article no. 60333 EAN 4250078166573 Brand **ICY BOX** Colour Black Material PC/ABS plastic Chipset DisplayLink DL6950

 $\label{eq:USBType-CTM} \textbf{USB Type-A interface to host PC are supported,}$ Input interface

both cables are included **Output interface** 2x DisplayPort™, vers. 1.2 interface (up to 2x 4096x2160@60 Hz)

6x USB 3.0 Type-A, 5x 5 V@0.9 A, 1x 5 V@1.5 A (BC 1.2) 1x Gigabit LAN RJ45 interface with wake-on-LAN function $1 \times 3.5 \text{ mm}$ microphone in jack, $1 \times 3.5 \text{ mm}$ audio out jack

Power supply Operating system System requirements

Video resolution

Dual mode: up to 2x 4096x2160@60 Hz

Single mode: up to 1x 5120x2880@@60 Hz (via two DisplayPort™

Data transfer rate USB 3.0: up to 5 Gbit/s, UASP supported

LAN: up to 10/100/1000 Mbit/s

External, AC 100-240 V / 1.3 A, 50/60 Hz, DC 20 V / 2.25 A,

total output 45 W, Level VI Windows® and macOS®

- Attached to a macOS® computer it does not support HDCP copy protected content (Blu-ray, Netflix, Amazon prime, etc.)

- Installed DisplayLink drivers

- To set up 4K/5K resolution, DisplayPort™ displays with 4K/5K and DisplayPort™ 1.2 support are needed

- The device is also compatible with Thunderbolt $^{\text{\tiny TM}}$ 3 Type-C $^{\text{\tiny TM}}$ equipped computers










ICY BOX IB-DK2242AC

DockingStation with Dual DisplayPort[™] interfaces



A bit of everything

With just one USB Type-A or Type-C ™ connector your notebook gains eleven additional ports: 6x USB 3.0, Gigabit LAN, 2x DisplayPort ™, as well as headphone and microphone ports. This makes the docking station a real general-purpose talent.



Stands firm

The high quality base ensures that the IB-DK2242AC does not get out of balance. Together with the variety of connections, it is a great team when it comes to keep your workplace tidy. This saves space and nerves.



High resolution

The IB-DK2242AC supports a resolution of up to 4K@60 Hz each for two monitors or one single 5K@60Hz display with two cables connected via DisplayPortTM. This sharpens your high resolution experience greatly.

Logistical data

 Packing unit:
 9 pcs./carton

 Total weight:
 12.3 kg/carton

 Gross weight: (with packing):
 1.290 kg

 Net weight:
 0.404 kg

Dimension/carton:
Dimension (with packing):
Dimension of article:
Country of origin:

500x310x310 mm 290x90x155 mm 195x70x125 mm China







RaidSonic Technology GmbH • Kurt-Fischer-Straße 50 • 22926 Ahrensburg / Germany
Telephone: +49-(0)4102 – 468 900 (Sales) • Fax: +49-(0)4102 – 468 901 • info@raidsonic.de • www.raidsonic.de
Offers and deliveries are only done under our General Terms and Conditions. Errors and omissions excepted.

